



DECLARATION OF PERFORMANCE
according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

No 341017

Easy Dicht 1K

Liquid applied water impermeable dispersion product with enhanced crack bridging ability at low temperatures (-20°C) and resistant against contact with chlorine water

**Ultrament GmbH & Co. KG
Müllerstraße 8
46242 Bottrop
Deutschland
Tel.: +49 (0) 2041 69 09 - 0
E-Mail: info@ultrament.de**

System 3

14891:2012


MPA TU Braunschweig
0761

Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Initial tensile adhesion strength	≥ 0,5 N/mm ²	system 3	14891:2012
Tensile adhesion strength after water contact	≥ 0,5 N/mm ²		
Tensile adhesion strength after heat ageing	≥ 0,5 N/mm ²		
Tensile adhesion strength after freeze-thaw cycles	≥ 0,5 N/mm ²		
Tensile adhesion strength after contact with lime water	no penetration		
Waterproofing	≥ 0,75 mm		
Crack bridging ability at normal conditions	NPD		
Tensile adhesion strength after chlorine water contact	≥ 0,5 N/mm ²		
Crack bridging ability at low temperatures (-5 °C)	≥ 0,75 mm		
Crack bridging ability at very low temperatures (-20°C)	≥ 0,75 mm		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Dr. Oliver Wowra
Leitung Technik

Bottrop 22.08.2018

